

# RODUCT INFORMATION

## **Product:**

Adjustable Basejack

### **Product Code:**

AOBJ01/AOBJ01-A

# **Product Description:**

Manufactured using a  $150 \times 150 \times 5$ mm flat plate, with  $38.1 \times 4$ mm thread welded to the centre of the plate, complete with a drop forged collar.

# Weight:

4.30 kg (6 tonne)

3.24kg (4 tonne)

## **Dimensions:**

650mm thread with an adjustment range of 500mm

# **Testing/Standards:**

BS4360/43A, BS1139 and EN74

Zinc plated to BS EN 12329:2000

# **Guidance:**

Transportation - care must be taken when transporting basejacks, ensuring that all components are secured in their storage and unable to become loose. Straps are used in appropriate areas and there is no risk of the strap fraying or becoming cut by any sharps.

Handling - care must be exercised when manually handling components, in line with manual handling procedures.

Storage - all components must be stored in a manner that limits any detrimental environmental effect due to weather or corrosive substances. Please note the safe working load on each storage component prior to loading and stacking.

Inspection - routine inspections should be scheduled, it is best practice to inspect basejacks before each work shift and after any occurrence which could affect the integrity. All jacks should be properly maintained and examined before use to ensure that the collar moves freely throughout the whole range of the thread.

Traceability - all basejacks supplied by Trademagic are fully traceable with unique identification code.

