

Product:

Extendable Hop Up Bracket (2+1)

Product Code :

AOHU03

Product Description:

Manufactured from U Channel and 48.3 x 3.2mm S355 galvanised tube and 38.1 x 3.2mm S355 tube, complete with a pear drop to act as an end stopper and specialized nut and bolt fixing which provides the ability to be extended and set at zero and one board. Complete with EN74 half-coupler.

Weight:

6.67kg

Dimensions:

From centre line of ledger connection 650mm (2 boards) and 900mm (3 boards)

Testing/Standards:

Tested to BS EN 12811

EN74

Zinc plated to BS EN 12329:2000

Guidance:

Transportation - care must be taken when transporting hop ups, ensuring that all components are secured in their storage and unable to become loose. Straps are used in appropriate areas and there is no risk of the strap fraying or becoming cut by any sharps.

Handling - care must be exercised when manually handling components, in line with manual handling procedures, in particular that the bolt is tightened sufficiently to avoid the extension sliding out.

Storage - all components must be stored in a manner that limits any detrimental environmental effect due to weather or corrosive substances. Please note the safe working load on each storage component prior to loading and stacking.

Inspection - routine inspections should be scheduled, it is best practice to inspect hop ups before each work shift and after any occurrence which could affect the integrity. All components should be properly maintained and examined before use.

Traceability - all transoms supplied by Trademagic are fully traceable with unique identification code.

