

Product:

Heavy Duty Steel Ladder Premium

Product Code :

AOGLB30/AOGLB35/AOGLB40/AOGLB50/AOGLB60/AOGLB70

Product Description:

Manufactured using 50 x 25 x 2mm S275 grade steel, with 28 x 1.5mm high grade anti-slip rungs with serrated finish exclusive to Trademagic. Ladder comes complete with domed rubber feet to prevent slips.

Dimensions:

410mm outer dimensions

Available in lengths of; 3m, 3.5m, 4m, 5m, 6m and 7m

Weight:

4.51kg per metre - based on an average across all sizes

Testing/Standards:

Tested to BS EN 131-1 2015+A1:2019

Galvanised to EN ISO 1461

Guidance:

Transportation - care must be taken when transporting ladders to ensure they are not bent beyond their elastic limits, while ensuring ladders are secured to the vehicle using straps at appropriate intervals. When ladders protrude above the height of the vehicle, care must be taken to ensure they do not exceed bridge height limits.

Handling - care must be exercised when manually handling ladders. It is recommended that ladders are held upright, not side on, and that two persons handle each beam, one at each end, where the weight lift is above 15kg.

Storage - ladders should be stored in a safe manner, horizontal with support at appropriate intervals to alleviate and damage or distortion.

Inspection - routine inspections should be scheduled, its is best practice to inspect ladder structures before each work shift and after any occurrence which could affect the integrity of the system.

Traceability - all ladders supplied by Trademagic are fully traceable with unique identification code.

