

Product:

Ladder Access Gate

Product Code :

AOLSG04/AOLSGP01

Product Description:

Manufactured using 25 x 25mm box section from, with 50 x 50mm pitch mesh and top and bottom toeboard to suit. Complete with double spring and EN74 couplers.

Weight:

9.00kg (Powder Coated)

10.00kg (Zinc Plated)

Dimensions:

960 x 600 x 800mm - inclusive of gate arm and fittings

Testing/Standards:

Tested to BS EN 12811

Powder coated to BS EN 13438

Zinc plated to BS EN 12329:2000

Guidance:

Transportation - care must be taken when transporting gates, ensuring that all components are secured in their storage and unable to become loose. Straps are used in appropriate areas and there is no risk of the strap fraying or becoming cut by any sharps.

Handling - care must be exercised when manually handling components, in line with manual handling procedures.

Storage - all components must be stored in a manner that limits any detrimental environmental effect due to weather or corrosive substances. Please note the safe working load on each storage component prior to loading and stacking.

Inspection - routine inspections should be scheduled, it is best practice to inspect gates before each work shift and after any occurrence which could affect the integrity.

All components should be properly maintained and examined before use to ensure that all couplers should be properly maintained and examined before use to ensure that there is a free-running, lightly lubricated, fit between the butts and bolts.

