

**Product:**

Light Steel Ladder

**Product Code :**

AOGLL30/AOGLL35/AOGLL40/AOGLL50/AOGLL60/AOGLL70

**Product Description:**

Manufactured using 62 x 25 x 1.5mm Q195 grade steel, with 22 x 22 x 1.2mm anti-slip rungs and end caps to prevent water, complete with large rubber domed feet bolted at both ends for ease of replacement. Supplied in a pre-galvanised finish.

**Dimensions:**

420mm outer dimensions

Available in lengths of; 3m, 3.5m, 4m, 5m, 6m and 7m

**Weight:**

4.35kg per metre - based on an average across all sizes

**Testing/Standards:**

Tested to BS EN 131-1 2015+A1:2019

**Guidance:**

Transportation - care must be taken when transporting ladders to ensure they are not bent beyond their elastic limits, while ensuring ladders are secured to the vehicle using straps at appropriate intervals. When ladders protrude above the height of the vehicle, care must be taken to ensure they do not exceed bridge height limits.

Handling - care must be exercised when manually handling ladders. It is recommended that ladders are held upright, not side on, and that two persons handle each beam, one at each end, where the weight lift is above 15kg.

Storage - ladders should be stored in a safe manner, horizontal with support at appropriate intervals to alleviate and damage or distortion.

Inspection - routine inspections should be scheduled, its is best practice to inspect ladder structures before each work shift and after any occurrence which could affect the integrity of the system.

Traceability - all ladders supplied by Trademagic are fully traceable with unique identification code.

