

Product:

Rigid Roadform

Product Code :

AORF04 - AORF06 - AORF08 - AORF10

Product Description:

Manufactured using 4.0mm U Channel at 3.0m in length and available in a variety of sizes including 4", 6", 8" and 10" widths. Complete with 22mm dowel holes and 3 stake housings which lock the Roadform Stakes/pins into place.

Weight:

21.00kg - 4" (100mm)

26.00kg - 6" (150mm)

32.00kg - 8" (200mm)

36.00kg - 10" (250mm)

Guidance:

Transportation - care must be taken when transporting roadforms, ensuring that all components are secured in their storage and unable to become loose. Straps are used in appropriate areas and there is no risk of the strap fraying or becoming cut by any sharps.

Handling - care must be exercised when manually handling roadforms. It is recommended that roadforms are held upright, not side on, and that two persons handle each roadform, one at each end, where the weight lift is above 15kg.

Storage - all components must be stored in a manner that limits any detrimental environmental effect due to weather or corrosive substances. Please note the safe working load on each storage component prior to loading and stacking. It is advised that roadforms are stored horizontally with support at appropriate intervals to alleviate any damage or distortion.

Inspection - routine inspections should be scheduled, it is best practice to inspect roadforms before each work shift and after any occurrence which could affect the integrity. All components should be properly maintained and examined before use.

